

(12) United States Patent Bergen

(45) Date of Patent:

(10) Patent No.:

US 11,106,936 B2

Aug. 31, 2021

(54) OBJECT POINT CLOUD COMPARISON AND MATCHING

- (71) Applicant: General Atomics, San Diego, CA (US)
- (72) Inventor: Zachary Bergen, Louisville, CO (US)
- Assignee: General Atomics, San Diego, CA (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 96 days.

- (21) Appl. No.: 16/561,403
- Sep. 5, 2019 Filed: (22)

Prior Publication Data (65)

US 2021/0073571 A1 Mar. 11, 2021

(51) Int. Cl. G06K 9/62 (2006.01)G06K 9/00 (2006.01)

(52) U.S. Cl. CPC G06K 9/6202 (2013.01); G06K 9/00201 (2013.01); G06K 9/6215 (2013.01)

(58) Field of Classification Search CPC . G06K 9/6202; G06K 9/00201; G06K 9/6215 See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

5.394.151 A	2/1995	Knaell
5,677,693 A		Frankot
6,864,828 B1		Golubiewski
7.046.841 B1	5/2005	
7,710,561 B2	5/2010	Roth

8,275,547	B2	9/2012	Rousselle
8,344,934	B2	1/2013	Ryland
9,417,323	B2	8/2016	Carande
2019/0205695	A1*	7/2019	Yan G06K 9/6215
2020/0273211	A1*	8/2020	Kato G06T 9/40

FOREIGN PATENT DOCUMENTS

CN	105844602 A	*	8/2016		
CN	109903319 A	*	6/2019		
WO	WO-2020154964 A1	*	8/2020	 G01S	17/931

OTHER PUBLICATIONS

Vlaminck, M., Luong H., and Philips, W., "Multi-resolution ICP for the efficient registration of point clouds based on octrees," 2017 Fifteenth IAPR International Conference on Machine Vision Applications (MVA), Nagoya, Japan, 2017, pp. 334-337, doi: 10.23919/ MVA.2017.7986869. (Year: 2017).*

* cited by examiner

Primary Examiner — Nancy Bitar Assistant Examiner — Daniella M. DiGuglielmo (74) Attorney, Agent, or Firm — Fitch, Even, Tabin & Flannery LLP

ABSTRACT (57)

Point clouds of objects are compared and matched using logical arrays based on the point clouds. The point clouds are azimuth aligned and translation aligned. The point clouds are converted into logical arrays for ease of processing. Then the logical arrays are compared (e.g. using the AND function and counting matches between the two logical arrays). The comparison is done at various quantization levels to determine which quantization level is likely to give the best object comparison result. Then the object comparison is made. More than two objects may be compared and the best match found.

18 Claims, 10 Drawing Sheets

